

Approved for healthy- and explosion prof cleaning

The IVB 7X M class is equipped with the unique EC drive motor system. This ensures long live time and enables use in ATEX zone 22 areas. The IVB 7X is approved according to ATEX directive 94/9/EC for the use in Zone 22.

The M class version is equipped with washable M-Class PET Fleece filter element - Easy and economical maintenance. The IVB 7 X offers features like 70 l. stainless steel container, tilt or lift off! And a robust steel frame. A filtration bag to be used for dust in class St1, St2, St3 in zone 22 A std. dust bag to be used for NON hazardous and NON ATEX dust.

- Safety vacuum cleaner for dustclass M ATEX Zone 22 approved
- single phase vacuum cleaner EC drive motor technology, long life / ATEX applications
- SoftStart: A gentle motor startup keeps the starting current low. For easy starting on limited electrical systems Auto On/Off. In combination with powered tools the machine starts and stops automatically when you start or stop the power tool Tilt or LiftOut container emptying.
- The 70 liter stainless steel container can be easily tilted in the frame or lifted off for emptying.



Picture shown may not represent model quoted

• Standard equipment

Included accessories		Ref. no.	Min. required	NILFISK IVB 7-M B1 230/1/50 EU
Filter				
	FILTER PET FLEECE M-CLASS D185X140	302000490	0	•
System TYPE 22 (ATEX) Hose Vacuum Cleaner				
	HOSE Ø36X4000MM W COUPLING TYPE 22	44193	0	•

Model	NILFISK IVB 7-M B1 230/1/50 EU
Ref. no.	302001895

PRODUCT FEATURES

Filter bag	•
Motor speed control	•
Automatic on/off - electric tools	•
ATEX hazardous TYPE 22 approval	•
Extra socket for tool	•



Approved for healthy- and explosion prof cleaning

Technical specifications

NILFISK IVB 7-M B1
230/1/50 EU

Grounded	YES
Voltage (V)	220-240
Frequency (Hz)	50-60
IP protection class	IP54
Dust class	M
Rated power (W)	1200
Suction power end of tube (W)	270
Airflow without hose (l/sec.)	56
Vacuum (kPa)	25
Vacuum max (kPa)	25
Sound pressure level at 1.5 m (dB(A) ISO 3744)	53.5
Container capacity (l)	70
Dust bag capacity (l)	40
Main filter type	PET
Main filter area (cm ²)	3000
Exhaust filter ULPA U15 (cm ²)	-
Inlet (mm)	50 type 22
Length x width x height (mm)	580x605x970
Weight (kg)	27.2

● Standard equipment, ○ Supplementary accessories, □ Mountable equipment

Accessories		Ref. no.	Min. required	NILFISK IVB 7-M B1 230/1/50 EU
System TYPE 22 (ATEX) Tube/Nozzle				
	BRUSH NOZZLE TYPE22 Ø36X230MM PE	44191	0	○
	COARSE DIRT NOZZLE TYPE22 Ø50X200MM ALU	42835	0	○
	CREVICE NOZZLE TYPE 22 Ø36 L290MM PLAST	44192	0	○
	CURVED EXTENSION TUBE TYPE22 Ø50X1100 S	33609	0	○



Approved for healthy- and explosion proof cleaning

Accessories		Ref. no.	Min. required	NILFISK IVB 7-M B1 230/1/50 EU
	DIAGONAL TUBE NOZZLE TYPE22 Ø36 RUBBER	302000227	0	○
	DIAGONAL TUBE NOZZLE TYPE22 Ø50 RUBBER	42836	0	○
	EXTENSION TUBE TYPE22 Ø36X950MM SS	46982	0	○
	FLAT NOZZLE TYPE22 Ø50MM RUBBER	42839	0	○
	FLOOR NOZZLE TYPE22 Ø36X450MM	302000369	0	○
	FLOOR NOZZLE TYPE22 Ø 50X500MM	42834	0	○
System TYPE 22 (ATEX) Hose Vacuum Cleaner				
	HOSE Ø36X4000MM W COUPLING TYPE 22	44193	0	●
	HOSE Ø50X4000MM CHIP TYPE 22	42825	0	○
	HOSE Ø50X8000MM CHIP TYPE 22	63710	0	○
Vacuum Accessory Set				
	TYPE 22 VACUUM SET Ø36MM 6-PCS	48907	0	○
Filter				
	FILTER PET FLEECE M-CLASS D185X140	302000490	0	●



Approved for healthy- and explosion prof cleaning

Accessories		Ref. no.	Min. required	NILFISK IVB 7-M B1 230/1/50 EU
Disposal Bag				
	DISPOSAL BAG ATTIX 7 5 PCS	302001480	0	○
Filter Bag				
	FLEECE FILTER BAG PU 5 PCS	302002892	0	○
	TER BAG ATTIX 7 5 PCS	302001484	0	○
Bag				
	FILTER BAG IVB-7 5 PCS	302001909	0	○

